



Series "PF" Polyester Foil Strain Gauge



Compatible adhesive & Operational temperature
 CN: -20~+80°C
 RP-2: -20~+80°C

Operational temperature -20~+80°C
 Temperature compensation range +10~+80°C

STEEL, CONCRETE, MORTAR MATERIALS USE

Gauge pattern	Type	Gauge size		Backing L W		Resistance in Ω
				L : length W : width (Unit : mm)		
<p>This is a foil strain gauge having polyester resin backing. It is mainly used for measurement on steel, concrete or mortar.</p>						
<p>●Single-element (G.F. 2.1 approx.)</p>						
 PFL-10-11	Single-element	10	0.9	17.5	5	120
 PFL-20-11		20	1.2	28	6	120
 PFL-30-11		30	2.3	40	7	120
<p>●90° 2-element Cross (G.F. 2.1 approx.)</p>						
 PFLC-20-11	90° 2-element Cross	20	1.2	28	28	120
 PFLC-30-11		30	2.3	40	40	120
<p>●45° /90° 3-element Rosette (G.F. 2.1 approx.)</p>						
 PFLR-20-11	45° /90° 3-element Rosette	20	1.2	28	28	120
 PFLR-30-11		30	2.3	40	40	120

Each package contains 10 gauges.

Series "PF"

Leadwire-integral Polyester Gauge





Compatible adhesive & Operational temperature
 CN: - 20~ + 80°C
 PR-2: - 20~ + 80°C

Operational temperature -20~+80°C

Temperature compensation range +10~+80°C

Quarter bridge with 3-wire system is usable to avoid an unexpected effect of resistance change with temperature.

STEEL, CONCRETE, MORTAR MATERIALS USE

Gauge pattern	Type	Gauge size		Backing		Resistance in Ω	
		L	W	L	W		
<p>This gauge has a pre-attached vinyl lead wire to PF series. Works for lead wire connection such as strain gauge terminal installation and lead wire soldering are not required. It saves much time and labor.</p> <ul style="list-style-type: none"> •Single-element (G.F. 2.1 approx.) 0.11mm² integral vinyl leadwire Total leadwire resistance per meter : 0.32Ω <p>2-wire system</p>  <p>PFL-10-11-1L</p> <p>3-wire system</p>  <p>PFL-10-11-3LT</p> <p>Each package contains 10 gauges. Other gauges of PF series are also available with leadwire-integral service, contact Altheris. PFLC-30-11, PFLR-30-11 are not available for the service.</p>		L : length	W : width	(Unit : mm)			
	PFL-10-11	-1L -3L	10	0.9	18	6	120
	PFL-20-11	-5L -3LT -5LT	20	1.2	28	6	120
	PFL-30-11		30	2.3	40	7	120

ALTHERIS bv

Scheveningseweg 15
 2517 KS DEN HAAG
 The Netherlands

+31 (0)70 3924421

+31 (0)70 3644249

Offices in : Benelux | Germany | France | UK | Italy | USA

www.altheris.com

sales@altheris.nl

LEADERS IN SENSORS & HEAVY DUTY JOYSTICKS

ALTHERIS
 SENSORS & CONTROLS